



Fast transient response, rush current protection 200mA LDO

MM3416 Series

Overview

This IC is a 200mA Low dropout regulator IC with Rush current protection circuit.
No load input current is 42μA typ. and it reduce drop voltage for high speed response.
Rush current protection circuit can control rush current.

Features

- Rush current protection
- High speed response
- High PSRR

Main specifications

($V_{DD}=V_{OUT}(Typ.)+1V$, $V_{CE}=V_{DD}$, $T_a=25^{\circ}C$ unless otherwise specified)

- Maximum rating supply voltage : -0.3V to 6.5V ($V_{DD}=5.5V$ at $4.5V \leq V_{OUT}$)
- Operating voltage range : 1.7V to 5.5V
- Operating ambient temperature : $-40^{\circ}C$ to $85^{\circ}C$
- Output current : 200mA
- Input current (OFF) : Typ. 0.1μA
- No-load input current : Typ. 42μA
- Output voltage range : 1V to 5V (0.05V step)
- Output voltage accuracy : $\pm 1\%$ ($2.0V \leq V_{OUT}(Typ.)$)
 $\pm 20mV$ ($V_{OUT}(Typ.) < 2.0V$)
- Line regulation : Typ. 0.05%/V ($V_{OUT}(Typ.) \leq 4.0V$, $V_{DD}=V_{OUT}(Typ.)+0.5V$ to 5.0V)
Typ. 0.05%/V ($4.0V < V_{OUT}(Typ.) \leq 4.5V$, $V_{DD}=V_{OUT}(Typ.)+0.5V$ to 5.5V)
Typ. 0.05%/V ($4.5V < V_{OUT}(Typ.)$, $V_{DD}=V_{OUT}(Typ.)+5.1V$ to 5.5V)
- Load regulation : Max. 40mV ($I_{OUT}=1mA$ to 150mA)
Max. 60mV ($I_{OUT}=1mA$ to 200mA)
- Dropout voltage : Typ. 0.3V ($I_{OUT}=200mA$, $V_{OUT}(Typ.)=3V$)
- PSRR : Typ. 75dB ($V_{OUT}(Typ.) \leq 4.0V$, $f=1kHz$)
Typ. 60dB ($4.0V < V_{OUT}(Typ.)$, $f=1kHz$)
- Output noise voltage : Typ. 60μVrms ($V_{OUT}(Typ.) \leq 4.0V$, $f_{BW}=10$ to 100kHz, $I_{OUT}=30mA$)
Typ. 90μVrms ($4.0V < V_{OUT}(Typ.)$, $f_{BW}=10$ to 100kHz, $I_{OUT}=30mA$)
- Output capacitor : 0.47μF (Ceramic capacitor)
- Protection function : Over current protection
- Additional function : ON/OFF control, Auto discharge

Packages

- SC-82ABB
- SOT-25A

Application

- Audio visual equipment
- Photographing / Imaging device
- Office equipment / Printer
- Home appliance equipment






Model Name

M M 3 4 1 6 X X X X X E
└──────────┘ └┘ └──┘ └┘ └┘
Series name (A) (B) (C) (D)


(A)	Function Type	A	CE=H active, with discharge function
		Z	
		C	CE=H active, without discharge function
		W	
(B)	Output voltage rank	10	(A)="A", "C" the output voltage can be designated in the range from 1.00V(10) to 5.00V(50) in 0.1V steps.
		┐	(A)="Z", "W" the output voltage can be designated in the range from 1.05V(10) to 4.95V(49) in 0.05V steps.
		50	
(C)	Package	U	SC-82ABB
		N	SOT-25A
(D)	Packing specifications	R	R housing (Standard)
		L	L housing

Block Diagram

- A, Z rank (CE=H active, with discharge function)




- C, W rank (CE=H active, without discharge function)






Pin Configuration

■ SC-82ABB



Pin No.	Pin name	Function
1	CE	ON/OFF-control pin (with CE pull-down resistor) Connect CE pin with VDD pin, when it is not used.
2	GND	GND pin
3	V _{OUT}	Output pin
4	V _{DD}	Voltage supply pin

■ SOT-25A



Pin No.	Pin name	Function
1	V _{DD}	Voltage supply pin
2	GND	GND pin
3	CE	ON/OFF-control pin (with CE pull-down resistor) Connect CE pin with VDD pin, when it is not used.
4	NC	No connection
5	V _{OUT}	Output pin





Absolute Maximum Ratings

Item		Symbol	Min.	Max.	Unit
Storage temperature		Tstg	-55	150	℃
Supply voltage		V _{DD}	-0.3	6.5	V
CE input voltage		V _{CE}	-0.3	6.5	V
Output current		I _{OUT}	0	300	mA
Power dissipation 1	SC-82ABB	Pd1	-	330	mW
*Note1	SOT-25A		-	350	mW
Power dissipation 2	SC-82ABB	Pd2	-	650	mW
*Note2	SOT-25A		-	700	mW

*Note1: With PC Board of glass epoxy

*Note2: JEDEC51-7 standard

Recommended Operating Conditions

Item	Symbol	Min.	Max.	Unit
Operating ambient temperature	Topr	-40	85	°C
Operating voltage	Vop	1.7	5.5	V
Output current	Iop	0	200	mA

Electrical Characteristics

(V_{DD}=V_{OUT}(Typ.)+1V, V_{CE}=V_{DD}, Ta=25°C unless otherwise specified)

(V_{DD}=5.5V at 4.5V≤V_{OUT})

Item	Symbol	Conditions	Min.	Typ.	Max.	Unit
Input current(OFF)	I _{DDOFF}	V _{CE} =0V	-	0.1	1.0	μA
No-Load Input Current	I _{DD}	I _{OUT} =0mA	-	42	64	μA
Output voltage	V _{OUT}	I _{OUT} =10mA 2.0V≤V _{OUT}	×0.99	-	×1.01	V
		I _{OUT} =10mA V _{OUT} <2.0V	-0.02	-	0.02	V
Line regulation	V _{LINE}	V _{OUT} (Typ.)+0.5V≤V _{DD} ≤5V V _{OUT} (Typ.)≤4.0V, I _{OUT} =1mA	-	0.05	0.10	% / V
		V _{OUT} (Typ.)+0.5V≤V _{DD} ≤5.5V 4.0V<V _{OUT} (Typ.)≤4.5V, I _{OUT} =1mA				
		5.1V≤V _{DD} ≤5.5V				
		4.5V<V _{OUT} (Typ.)≤5.0V, I _{OUT} =1mA				
Load regulation 1	V _{LOAD1}	1mA≤I _{OUT} ≤150mA	-	-	40	mV
Load regulation 2	V _{LOAD2}	1mA≤I _{OUT} ≤200mA	-	-	60	mV
Dropout voltage	V _{IO}	Please refer to another page.	-	-	-	V
Output short-circuit current *Note3	I _{lim}	V _{OUT} =0V	-	50	-	mA

*Note3: The parameter is guaranteed by design.



Electrical Characteristics

($V_{DD}=V_{OUT}(Typ.)+1V$, $V_{CE}=V_{DD}$, $T_a=25^{\circ}C$ unless otherwise specified)

($V_{DD}=5.5V$ at $4.5V \leq V_{OUT}$)

項目	記号	条件	Min.	Typ.	Max.	単位
Vout temperature coefficient *Note3	$\Delta V_{OUT} / \Delta T_{OP}$	$I_{OUT}=10mA$ $-40 \leq T_{OP} \leq 85^{\circ}C$	-	± 100	-	ppm/ $^{\circ}C$
Ripple rejection *Note3	RR	$f=1kHz$, $V_{ripple}=0.5V$ $I_{OUT}=30mA$, $V_{OUT}(Typ.) \leq 4.0V$	-	75	-	dB
		$f=1kHz$, $V_{ripple}=0.5V$ $I_{OUT}=30mA$, $4.0V < V_{OUT}(Typ.)$	-	60	-	
Output noise voltage *Note3	Vn	$V_{OUT}(Typ.) \leq 4.0V$, $I_{OUT}=30mA$ $f_{BW}=10 \sim 100kHz$	-	60	-	μV_{rms}
		$4.0V < V_{OUT}(Typ.)$, $I_{OUT}=30mA$ $f_{BW}=10 \sim 100kHz$	-	90	-	
CE pin current *Note3	I_{CE}		-	0.5	-	μA
CE High threshold voltage	V_{CEH}		1.5	-	5.5	V
CE Low threshold voltage	V_{CEL}		0	-	0.3	V
CE pin transient response *Note3	t_{CE}	$I_{OUT}=50mA$	-	30	-	μs
Output NMOS ON resistance *Note3,4	R_{DON}	$V_{CE}=0V$, $V_{DD}=4V$	-	20	-	Ω
		$4.0V < V_{OUT}(Typ.)$ $V_{CE}=0V$, $V_{DD}=5.5V$				

*Note3: This parameter is guaranteed by design.

*Note4: This parameter is only MM3416A/Z series.





Electrical Characteristics

($V_{DD}=V_{OUT}(\text{Typ.})+1\text{V}$, $V_{CE}=V_{DD}$, $T_a=25^\circ\text{C}$ unless otherwise specified)

($V_{DD}=5.5\text{V}$ at $4.5\text{V}\leq V_{OUT}$)

Model name	Item							
	Output voltage				Dropout voltage			
	V_{OUT} (V)				V_{IO} (V)			
	Conditions	Min.	Typ.	Max.	Conditions	Min.	Typ.	Max.
MM3416A/C10	$I_{OUT}=10\text{mA}$	0.980	1.000	1.020	$I_{OUT}=150\text{mA}$ $1.0\text{V}\leq V_{OUT}(\text{Typ.})<1.8\text{V}$ *Note5	-	0.63	0.70
MM3416Z/W10		1.030	1.050	1.070				
MM3416A/C11		1.080	1.100	1.120				
MM3416Z/W11		1.130	1.150	1.170				
MM3416A/C12		1.180	1.200	1.220				
MM3416Z/W12		1.230	1.250	1.270				
MM3416A/C13		1.280	1.300	1.320				
MM3416Z/W13		1.330	1.350	1.370				
MM3416A/C14		1.380	1.400	1.420				
MM3416Z/W14		1.430	1.450	1.470				
MM3416A/C15		1.480	1.500	1.520				
MM3416Z/W15		1.530	1.550	1.570				
MM3416A/C16		1.580	1.600	1.620				
MM3416Z/W16		1.630	1.650	1.670				
MM3416A/C17		1.680	1.700	1.720				
MM3416Z/W17		1.730	1.750	1.770				
MM3416A/C18		1.780	1.800	1.820	$I_{OUT}=150\text{mA}$ $1.8\text{V}\leq V_{OUT}$ $V_{DD}=V_{OUT}(\text{Typ.})-0.2\text{V}$	-	0.53	0.60
MM3416Z/W18		1.830	1.850	1.870				
MM3416A/C19		1.880	1.900	1.920				
MM3416Z/W19		1.930	1.950	1.970				
MM3416A/C20		1.980	2.000	2.020				
MM3416Z/W20		2.030	2.050	2.071				
MM3416A/C21		2.079	2.100	2.121				
MM3416Z/W21		2.129	2.150	2.172				
MM3416A/C22		2.178	2.200	2.222				
MM3416Z/W22		2.228	2.250	2.273				
MM3416A/C23		2.277	2.300	2.323				
MM3416Z/W23		2.327	2.350	2.374				
MM3416A/C24		2.376	2.400	2.424				
MM3416Z/W24		2.426	2.450	2.475				
MM3416A/C25		2.475	2.500	2.525				
MM3416Z/W25		2.525	2.550	2.576				
MM3416A/C26		2.574	2.600	2.626				
MM3416Z/W26		2.624	2.650	2.677				
MM3416A/C27		2.673	2.700	2.727				
MM3416Z/W27		2.723	2.750	2.778				
MM3416A/C28		2.772	2.800	2.828				
MM3416Z/W28		2.822	2.850	2.879				
MM3416A/C29		2.871	2.900	2.929				
MM3416Z/W29		2.921	2.950	2.980				
MM3416A/C30		2.970	3.000	3.030				
MM3416Z/W30		3.020	3.050	3.081				

*Note5: Dropout voltage MAX value in the input and it is confirmed that there is no output abnormal voltage impression the load 150mA in the model less than $V_{out}<1.8\text{V}$.





Electrical Characteristics

($V_{DD}=V_{OUT}(Typ.)+1V$, $V_{CE}=V_{DD}$, $T_a=25^{\circ}C$ unless otherwise specified)

($V_{DD}=5.5V$ at $4.5V \leq V_{OUT}$)

Model name	Item							
	Output voltage				Dropout voltage			
	V_{OUT} (V)				V_{IO} (V)			
	Conditions	Min.	Typ.	Max.	Conditions	Min.	Typ.	Max.
MM3416A/C31	$I_{OUT}=10mA$	3.069	3.100	3.131	$I_{OUT}=150mA$ $3.1V \leq V_{OUT}$ $V_{DD}=V_{OUT}(Typ.)-0.2V$	-	0.21	0.27
MM3416Z/W31		3.119	3.150	3.182				
MM3416A/C32		3.168	3.200	3.232				
MM3416Z/W32		3.218	3.250	3.283				
MM3416A/C33		3.267	3.300	3.333				
MM3416Z/W33		3.317	3.350	3.384				
MM3416A/C34		3.366	3.400	3.434				
MM3416Z/W34		3.416	3.450	3.485				
MM3416A/C35		3.465	3.500	3.535				
MM3416Z/W35		3.515	3.550	3.586				
MM3416A/C36		3.564	3.600	3.636				
MM3416Z/W36		3.614	3.650	3.687				
MM3416A/C37		3.663	3.700	3.737				
MM3416Z/W37		3.713	3.750	3.788				
MM3416A/C38		3.762	3.800	3.838				
MM3416Z/W38		3.812	3.850	3.889				
MM3416A/C39		3.861	3.900	3.939				
MM3416Z/W39		3.911	3.950	3.990				
MM3416A/C40		3.960	4.000	4.040				
MM3416Z/W40		4.010	4.050	4.091				
MM3416A/C41		4.059	4.100	4.141				
MM3416Z/W41		4.109	4.150	4.192				
MM3416A/C42		4.158	4.200	4.242				
MM3416Z/W42		4.208	4.250	4.293				
MM3416A/C43		4.257	4.300	4.343				
MM3416Z/W43		4.307	4.350	4.394				
MM3416A/C44		4.356	4.400	4.444				
MM3416Z/W44		4.406	4.450	4.495				
MM3416A/C45		4.455	4.500	4.545				
MM3416Z/W45		4.505	4.550	4.596				
MM3416A/C46		4.554	4.600	4.646				
MM3416Z/W46		4.604	4.650	4.697				
MM3416A/C47		4.653	4.700	4.747				
MM3416Z/W47		4.703	4.750	4.798				
MM3416A/C48		4.752	4.800	4.848				
MM3416Z/W48		4.802	4.850	4.899				
MM3416A/C49		4.851	4.900	4.949				
MM3416Z/W49		4.901	4.950	5.000				
MM3416A/C50		4.950	5.000	5.050		-	0.18	0.25





Electrical Characteristics

($V_{DD}=V_{OUT}(Typ.)+1V$, $V_{CE}=V_{DD}$, $T_a=25^{\circ}C$ unless otherwise specified)

($V_{DD}=5.5V$ at $4.5V \leq V_{OUT}$)

Model name	Item							
	Output voltage				Dropout voltage			
	V _{OUT} (V)				V _{IO} (V)			
	Conditions	Min.	Typ.	Max.	Conditions	Min.	Typ.	Max.
MM3416A/C10	I _{OUT} =10mA	0.980	1.000	1.020	I _{OUT} =200mA 1.0V≤ V _{OUT} (Typ.)<2.1V *Note6	-	0.85	0.98
MM3416Z/W10		1.030	1.050	1.070				
MM3416A/C11		1.080	1.100	1.120				
MM3416Z/W11		1.130	1.150	1.170				
MM3416A/C12		1.180	1.200	1.220				
MM3416Z/W12		1.230	1.250	1.270				
MM3416A/C13		1.280	1.300	1.320				
MM3416Z/W13		1.330	1.350	1.370				
MM3416A/C14		1.380	1.400	1.420				
MM3416Z/W14		1.430	1.450	1.470				
MM3416A/C15		1.480	1.500	1.520				
MM3416Z/W15		1.530	1.550	1.570				
MM3416A/C16		1.580	1.600	1.620				
MM3416Z/W16		1.630	1.650	1.670				
MM3416A/C17		1.680	1.700	1.720				
MM3416Z/W17		1.730	1.750	1.770				
MM3416A/C18		1.780	1.800	1.820				
MM3416Z/W18		1.830	1.850	1.870				
MM3416A/C19		1.880	1.900	1.920				
MM3416Z/W19		1.930	1.950	1.970				
MM3416A/C20		1.980	2.000	2.020				
MM3416Z/W20		2.030	2.050	2.071				
MM3416A/C21	2.079	2.100	2.121	I _{OUT} =200mA 2.1V≤V _{OUT} V _{DD} =V _{OUT} (Typ.)-0.2V	-	0.49	0.59	
MM3416Z/W21	2.129	2.150	2.172					
MM3416A/C22	2.178	2.200	2.222					
MM3416Z/W22	2.228	2.250	2.273					
MM3416A/C23	2.277	2.300	2.323					
MM3416Z/W23	2.327	2.350	2.374					
MM3416A/C24	2.376	2.400	2.424					
MM3416Z/W24	2.426	2.450	2.475					
MM3416A/C25	2.475	2.500	2.525					
MM3416Z/W25	2.525	2.550	2.576					
MM3416A/C26	2.574	2.600	2.626					
MM3416Z/W26	2.624	2.650	2.677					
MM3416A/C27	2.673	2.700	2.727					
MM3416Z/W27	2.723	2.750	2.778					
MM3416A/C28	2.772	2.800	2.828					
MM3416Z/W28	2.822	2.850	2.879					
MM3416A/C29	2.871	2.900	2.929					
MM3416Z/W29	2.921	2.950	2.980					
MM3416A/C30	2.970	3.000	3.030					
MM3416Z/W30	3.020	3.050	3.081					

*Note6: Dropout voltage MAX value in the input and it is confirmed that there is no output abnormal voltage impression the load 200mA in the model less than $V_{out} < 2.1V$.





Electrical Characteristics


($V_{DD}=V_{OUT}(Typ.)+1V$, $V_{CE}=V_{DD}$, $T_a=25^{\circ}C$ unless otherwise specified)

($V_{DD}=5.5V$ at $4.5V \leq V_{OUT}$)


Model name	Item							
	Output voltage				Dropout voltage			
	V_{OUT} (V)				V_{IO} (V)			
	Conditions	Min.	Typ.	Max.	Conditions	Min.	Typ.	Max.
MM3416A/C31	$I_{OUT}=10mA$	3.069	3.100	3.131	$I_{OUT}=200mA$ $3.1V \leq V_{OUT}$ $V_{DD}=V_{OUT}(Typ.)-0.2V$			
MM3416Z/W31		3.119	3.150	3.182				
MM3416A/C32		3.168	3.200	3.232				
MM3416Z/W32		3.218	3.250	3.283				
MM3416A/C33		3.267	3.300	3.333				
MM3416Z/W33		3.317	3.350	3.384				
MM3416A/C34		3.366	3.400	3.434				
MM3416Z/W34		3.416	3.450	3.485				
MM3416A/C35		3.465	3.500	3.535				
MM3416Z/W35		3.515	3.550	3.586				
MM3416A/C36		3.564	3.600	3.636				
MM3416Z/W36		3.614	3.650	3.687				
MM3416A/C37		3.663	3.700	3.737				
MM3416Z/W37		3.713	3.750	3.788				
MM3416A/C38		3.762	3.800	3.838				
MM3416Z/W38		3.812	3.850	3.889				
MM3416A/C39		3.861	3.900	3.939				
MM3416Z/W39		3.911	3.950	3.990				
MM3416A/C40		3.960	4.000	4.040				
MM3416Z/W40		4.010	4.050	4.091				
MM3416A/C41		4.059	4.100	4.141				
MM3416Z/W41		4.109	4.150	4.192				
MM3416A/C42		4.158	4.200	4.242				
MM3416Z/W42		4.208	4.250	4.293				
MM3416A/C43		4.257	4.300	4.343				
MM3416Z/W43		4.307	4.350	4.394				
MM3416A/C44		4.356	4.400	4.444				
MM3416Z/W44		4.406	4.450	4.495				
MM3416A/C45		4.455	4.500	4.545				
MM3416Z/W45		4.505	4.550	4.596				
MM3416A/C46		4.554	4.600	4.646				
MM3416Z/W46		4.604	4.650	4.697				
MM3416A/C47		4.653	4.700	4.747				
MM3416Z/W47		4.703	4.750	4.798				
MM3416A/C48		4.752	4.800	4.848				
MM3416Z/W48		4.802	4.850	4.899				
MM3416A/C49		4.851	4.900	4.949				
MM3416Z/W49		4.901	4.950	5.000				
MM3416A/C50		4.950	5.000	5.050		-	0.25	0.35



Test Circuit



Application Circuit



(Example of external parts)

- Output capacitor Ceramic capacitor 0.47 μ F
- Input capacitor Ceramic capacitor 0.47 μ F *Temperature characteristics : B

- In the event a problem which may affect industrial property or any other rights of us or a third party is encountered during the use of information described in these circuit, we shall not be liable for any such problem, nor grant a license therefore.





Note

1. Please use this IC within the stated absolute maximum ratings.
The IC is liable to malfunction should the ratings be exceeded.
2. Due to restrictions on the package power dissipation, the output current value may not be satisfied.
Attention should be paid to the power dissipation of the package when the output current is large or the voltage between Iinput and Output is high.
3. The output capacitor is required between output and GND to prevent oscillation.
4. The ESR of capacitor must be defined in ESR stability area.
It is possible to use a ceramic capacitor without ESR resistance for output.
The ceramic capacitor must be used more than 0.47 μ F and B temperature characteristics.
5. The wire of VDD and GND is required to print full ground plane for noise and stability.
6. The input capacitor must be connected a distance of less than 1cm from input pin.
7. It is able to oscillation when you use the capacitor with intense capacitance change such as micro.
Please evaluate IC in the set.
8. In case the output voltage is above the input voltage, the overcurrent flow by internal parastic diode from output to input.
In such application, the external bypass diode must be connected between output and input pin.
9. This IC will limit the output current with the overcurrent protection circuit when the overcurrent and the output do short-circuit.
However, IC generates heat because of the substrate and use conditions and there is a possibility of destroying it exceeding a permissible loss.
The characteristic changes depending on the substrate condition.
Please evaluate IC in the set.



About Power Dissipation

The Power dissipation change if board to mount IC change because radiative heat fix at board.
It is reference data below, Evaluate IC in the set.

■ SC-82ABB

1. PC Board of glass epoxy


Board size 110mm×40mm t=0.8mm

Power dissipation 330mW Ta=25℃

2. JEDEC51-7 standard (4 layer FR-4 board)

Board size 114.3mm×76.2mm t=1.6mm Copper foil area 80%

Power dissipation 650mW Ta=25℃



■ SOT-25A

1. PC Board of glass epoxy


Board size 60mm×40mm t=1.6mm Copper foil area 60%

Power dissipation 350mW Ta=25℃

2. JEDEC51-7 standard (4 layer FR-4 board)

Board size 114.3mm×76.2mm t=1.6mm Copper foil area 80%

Power dissipation 700mW Ta=25℃



It is recommended to layout the VIA for heat radiation in the GND pattern of reverse (of IC) when there is the GND pattern in the inner layer (in using multiplayer substrate).
By increasing these copper foil pattern area of PCB, Power dissipation improves.





About Power Dissipation

The thermal shut down circuit is not composed in MM3416.


So IC is able to be destroyed if the IC's heat more than power dissipation when output resistance is half short($1.8\sim3.6\Omega$).

Evaluate IC in the set.

The current limit characteristic of MM3416($V_o=4.0V$) is shown below.

Output voltage is about 1.0V when output is half short($1.8\sim3.6\Omega$).

Be care of destruction by great heat in area that Output voltage is about 1.0V.








The current limit operate in this area (half short $1.8\sim3.6\Omega$).
Be care of IC's heat is great.





Typical Performance Characteristics (1.0V)




$(V_{DD}=V_{OUT(Typ.)}+1V, V_{CE}=V_{DD}, T_a=25^{\circ}C \text{ unless otherwise specified})$





Typical Performance Characteristics (1.0V)

$(V_{DD}=V_{OUT(Typ.)}+1V, V_{CE}=V_{DD}, T_a=25^{\circ}C \text{ unless otherwise specified})$






Typical Performance Characteristics (1.0V)

($V_{DD}=V_{OUT(Typ.)}+1V$, $V_{CE}=V_{DD}$, $T_a=25^{\circ}C$ unless otherwise specified)


Load transient response

($V_{DD}=V_{OUT}+1V$, $V_{CE}=V_{DD}$, $C_{in}=0.47\mu F$)


$I_{OUT} : 50mA \leftrightarrow 100mA$




$I_{OUT} : 50mA \leftrightarrow 150mA$



$I_{OUT} : 0.1mA \leftrightarrow 50mA$




$I_{OUT} : 0.1mA \leftrightarrow 150mA$




Input rise characteristics

($V_{DD}=0V \rightarrow 2V$, $V_{CE}=V_{DD}$, $I_{OUT}=50mA$)



CE rise characteristics

($V_{DD}=2V$, $V_{CE}=0V \rightarrow V_{DD}$, $I_{OUT}=50mA$)







Typical Performance Characteristics (1.0V)

($V_{DD}=V_{OUT(Typ.)}+1V$, $V_{CE}=V_{DD}$, $T_a=25^{\circ}C$ unless otherwise specified)



Output Rise Time

($V_{DD}=V_{OUT}+1V$, $V_{CE}=0 \rightarrow V_{DD}$, $C_{in}=0.47\mu F$)




Rush Current

($V_{DD}=V_{OUT}+1V$, $V_{CE}=0 \rightarrow V_{DD}$, $C_{in}=0.47\mu F$)




Output Rise & Rush Current

($V_{DD}=2V$, $V_{CE}=0 \rightarrow 2V$, $C_{in}=0.47\mu F$, $C_o=1000\mu F$)









($V_{DD}=2V$, $V_{CE}=0 \rightarrow 2V$, $C_{in}=0.47\mu F$, $C_o=47\mu F$)








Typical Performance Characteristics (3.0V)

$(V_{DD}=V_{OUT(Typ.)}+1V, V_{CE}=V_{DD}, T_a=25^{\circ}C \text{ unless otherwise specified})$



Typical Performance Characteristics (3.0V)

$(V_{DD}=V_{OUT(Typ.)}+1V, V_{CE}=V_{DD}, T_a=25^{\circ}C \text{ unless otherwise specified})$




Typical Performance Characteristics (3.0V)

($V_{DD}=V_{OUT(Typ.)}+1V$, $V_{CE}=V_{DD}$, $T_a=25^{\circ}C$ unless otherwise specified)


Load transient response

($V_{DD}=V_{OUT}+1V$, $V_{CE}=V_{DD}$, $C_{in}=0.47\mu F$)


$I_{OUT} : 50mA \leftrightarrow 100mA$




$I_{OUT} : 50mA \leftrightarrow 150mA$



$I_{OUT} : 0.1mA \leftrightarrow 50mA$




$I_{OUT} : 0.1mA \leftrightarrow 150mA$




Input rise characteristics

($V_{DD}=0V \rightarrow 4V$, $V_{CE}=V_{DD}$, $I_{OUT}=50mA$)



CE rise characteristics

($V_{DD}=4V$, $V_{CE}=0V \rightarrow V_{DD}$, $I_{OUT}=50mA$)





Typical Performance Characteristics (3.0V)

$(V_{DD}=V_{OUT(Typ.)}+1V, V_{CE}=V_{DD}, T_a=25^{\circ}C \text{ unless otherwise specified})$



Output Rise Time

$(V_{DD}=V_{OUT}+1V, V_{CE}=0 \rightarrow V_{DD}, C_{in}=0.47\mu F)$




Rush Current

$(V_{DD}=V_{OUT}+1V, V_{CE}=0 \rightarrow V_{DD}, C_{in}=0.47\mu F)$




Output Rise & Rush Current

$(V_{DD}=4V, V_{CE}=0 \rightarrow 4V, C_{in}=0.47\mu F, C_o=1000\mu F)$









$(V_{DD}=4V, V_{CE}=0 \rightarrow 4V, C_{in}=0.47\mu F, C_o=47\mu F)$








Typical Performance Characteristics (4.0V)

$(V_{DD}=V_{OUT(Typ.)}+1V, V_{CE}=V_{DD}, T_a=25^{\circ}C \text{ unless otherwise specified})$



Typical Performance Characteristics (4.0V)

$(V_{DD}=V_{OUT(Typ.)}+1V, V_{CE}=V_{DD}, T_a=25^{\circ}C \text{ unless otherwise specified})$






Typical Performance Characteristics (4.0V)

($V_{DD}=V_{OUT(Typ.)}+1V$, $V_{CE}=V_{DD}$, $T_a=25^\circ\text{C}$ unless otherwise specified)


Load transient response

($V_{DD}=V_{OUT}+1V$, $V_{CE}=V_{DD}$, $C_{in}=0.47\mu\text{F}$)


$I_{OUT} : 50\text{mA} \leftrightarrow 100\text{mA}$




$I_{OUT} : 50\text{mA} \leftrightarrow 150\text{mA}$



$I_{OUT} : 0.1\text{mA} \leftrightarrow 50\text{mA}$




$I_{OUT} : 0.1\text{mA} \leftrightarrow 150\text{mA}$




Input rise characteristics

($V_{DD}=0V \rightarrow 5V$, $V_{CE}=V_{DD}$, $I_{OUT}=50\text{mA}$)



CE rise characteristics

($V_{DD}=5V$, $V_{CE}=0V \rightarrow V_{DD}$, $I_{OUT}=50\text{mA}$)







Typical Performance Characteristics (4.0V)

($V_{DD}=V_{OUT(Typ.)}+1V$, $V_{CE}=V_{DD}$, $T_a=25^{\circ}C$ unless otherwise specified)



Output Rise Time

($V_{DD}=V_{OUT}+1V$, $V_{CE}=0 \rightarrow V_{DD}$, $C_{in}=0.47\mu F$)




Rush Current

($V_{DD}=V_{OUT}+1V$, $V_{CE}=0 \rightarrow V_{DD}$, $C_{in}=0.47\mu F$)




Output Rise & Rush Current

($V_{DD}=5V$, $V_{CE}=0 \rightarrow 5V$, $C_{in}=0.47\mu F$, $C_o=1000\mu F$)









($V_{DD}=5V$, $V_{CE}=0 \rightarrow 5V$, $C_{in}=0.47\mu F$, $C_o=47\mu F$)



Typical Performance Characteristics (5.0V)




($V_{DD}=V_{OUT(Typ.)}+1V$, $V_{CE}=V_{DD}$, $T_a=25^{\circ}C$ unless otherwise specified)





Typical Performance Characteristics (5.0V)

$(V_{DD}=V_{OUT(Typ.)}+1V, V_{CE}=V_{DD}, T_a=25^{\circ}C \text{ unless otherwise specified})$






Typical Performance Characteristics (5.0V)

$(V_{DD}=V_{OUT(Typ.)}+1V, V_{CE}=V_{DD}, T_a=25^{\circ}C \text{ unless otherwise specified})$


Load transient response

$(V_{DD}=V_{OUT}+1V, V_{CE}=V_{DD}, C_{in}=0.47\mu F)$


$I_{OUT} : 50mA \leftrightarrow 100mA$




$I_{OUT} : 50mA \leftrightarrow 150mA$



$I_{OUT} : 0.1mA \leftrightarrow 50mA$




$I_{OUT} : 0.1mA \leftrightarrow 150mA$




Input rise characteristics

$(V_{DD}=0V \rightarrow 5.5V, V_{CE}=V_{DD}, I_{OUT}=50mA)$



CE rise characteristics

$(V_{DD}=5.5V, V_{CE}=0V \rightarrow V_{DD}, I_{OUT}=50mA)$







Typical Performance Characteristics (5.0V)

$(V_{DD}=V_{OUT(Typ.)}+1V, V_{CE}=V_{DD}, T_a=25^{\circ}C \text{ unless otherwise specified})$



Output Rise Time

$(V_{DD}=V_{OUT}+1V, V_{CE}=0 \rightarrow V_{DD}, C_{in}=0.47\mu F)$




Rush Current

$(V_{DD}=V_{OUT}+1V, V_{CE}=0 \rightarrow V_{DD}, C_{in}=0.47\mu F)$



Output Rise & Rush Current

$(V_{DD}=5.5V, V_{CE}=0 \rightarrow 5.5V, C_{in}=0.47\mu F, C_o=1000\mu F)$



$(V_{DD}=5.5V, V_{CE}=0 \rightarrow 5.5V, C_{in}=0.47\mu F, C_o=47\mu F)$

