FEATURES


- · Ultra Low Dropout Voltage
- Compatible with low ESR MLCC as Input / Output Capacitor
- · Good Line and Load Regulation
- · Guaranteed Output Current of 1A
- Available in SOP8, SOP8-PP, SOT-89-5L, DFN2X3-8L Packages
- Fixed Output: 1.0V, 1.2V, 1.5V, 1.8V, 2.5V, and 3.3V
- · VOUT Power OK Signal
- · Programmable Soft-Start Function
- · Output Auto Discharge Function
- Over-Temperature/Over-Current Protection

APPLICATION

- · LCD TVs and SETTOP Boxes
- Battery Powered Equipment
- · Motherboards and Graphic Cards
- · Microprocessor Power Supplies
- · Peripheral Cards
- · High Efficiency Linear Regulators
- · Battery Chargers

DESCRIPTION

The TJ4310 series of high performance ultra-low dropout linear regulators operates from 2.5V to 5.5V input supply and provides ultra-low dropout voltage, high output current with low ground current. Wide range of preset output voltage options are available. These ultra-low dropout linear regulators respond fast to step changes in load which makes them suitable for low voltage micro-processor applications. The TJ4310 is developed on a CMOS process technology which allows low quiescent current operation independent of output load current. This CMOS process also allows the TJ4310 to operate under extremely low dropout conditions.



ORDERING INFORMATION

Device	Package		
TJ4310GD-ADJ	SOP8		
TJ4310GD-X.X			
TJ4310GDP-ADJ	SOP8-PP		
TJ4310GDP-X.X			
TJ4310GF-ADJ	SOT-89-5L		
TJ4310GQ-ADJ	DFN2X3-8L		

X.X = Output Voltage = 1.0, 1.2, 1.5, 1.8, 2.5, and 3.3

ABSOLUTE MAXIMUM RATINGS (Note 1)

CHARACTERISTIC	SYMBOL	MIN.	MAX.	UNIT
Input Supply Voltage (Survival)	V _{IN}	-	6.5	V
Maximum Output Current	I _{MAX}	-	1	Α
Lead Temperature (Soldering, 5 sec)	T _{SOL}		260	°C
Storage Temperature Range	T _{STG}	-65	150	°C
Operating Junction Temperature Range	T _{JOPR}	-40	125	°C
Package Thermal Resistance *	OJA-SOP8-PP	68		°C/W

^{*} Calculated from package in still air, mounted to 2.6mm X 3.5mm(minimum foot print) 2 layer PCB without thermal vias per JESD51 standards.

